

P1 METER

HMeter-P1-W



Features

<p>01 Quick Installation <i>Plug-and-play RJ12 connection to smart meter P1 port</i></p>	<p>03 High Compatibility <i>Works with DSMR 4.X/5.0 protocols</i></p>
<p>02 High Data Sampling Rate <i>Supports data sampling rate up to 1 time/second</i></p>	<p>04 Dual Wireless Connectivity <i>Wi-Fi + Bluetooth for more flexible data viewing</i></p>

Technical Specifications

Model	HMeter-P1-W
Compatibility	Works with DSMR 4.x/5.0 single-phase and three-phase smart meters
Data sampling rate	Every second (DSMR 5.0) Every 10 seconds (DSMR 4.x)
Interface	RJ12
Communication method	Wi-Fi
Wi-Fi range (m)*	30 (Indoor) 50 (Outdoor)
Bluetooth protocol	Bluetooth 5.0
Power consumption	< 1.5 W Typical value: 5 V / 260 mA
Net weight (g)	22
Working temperature range (°C)	-25 to +55
Storage temperature range (°C)	-25 to +55
Working humidity range	≤ 85% RH (No condensing)
Storage humidity range	40% to 85% RH (No condensing)
Working altitude (m)	≤ 2000
Enclosure rating	IP20 (Indoor)

* The actual range may vary depending on local environmental conditions.