

PRODUCTSHEET

ALP DC MINI

Electrical Vehicle Charger



ALP DC MINI

Electric Vehicle Charger - product specification


www.alp-ev.com

ALPEV
Taking charge of e-mobility

ALP DC MINI

Highlights

Wall-mounted DC charger’s standout feature lies in its compact design, ensuring easy installation anywhere, while delivering up to 40 kW of power with CCS2 plug compatibility.



Charging with up to 40 kW DC



Online via cellular, WLAN and LAN



Hardware Ready for ISO 15118



Remote load management via OCPP



7" display



Technical data	
Max. charging power per charging point	Up to 40 kW DC output
Charging connector	Single CCS2 Cable
Protection Class	IP 54, IK 10
Connectivity (Optional)	Wifi, LAN, LTE
IT backend connection	OCPP 1.6J
Meter	MID meter (Option) Eichrecht compatible (Q2 / 2025)
Energy-/load management	via OCPP
Authorisation	RFID, Credit Card Terminal(Optional), OCPP
User Interface	7" TFT, LED
Credit Card Reader	Optional (Payter Apollo)
Cable Management	With hook
Dimensions	635 x 630 x 249mm
Operational Conditions	-35 C to +50 C



ALP DC CHARGING SOLUTIONS

Carefree electric driving with
the smartest charging solutions



Leursebaan 266, 4814 RE Breda, The Netherlands
sales@alp-ev.com | +31(0)85-2465771



www.alp-ev.com



Distributeur: VDH Solar Groothandel B.V.
Finlandlaan 1, 2391 PV Hazerswoude-Dorp, Holland
+31 (0)172 235 990 | info@vdh-solar.nl | www.vdh-solar.nl